

EXECUTING THE SAME BINARY ON SEVERAL OPERATING SYSTEMS

STEFFEN GRØNNEBERG (STEFFENG@MATH.UIO.NO)

ABSTRACT. We present a hack that creates a binary file executable both on Windows and ELF-based systems. It can be used to create software installers and other applications not exceeding 64 kilo bytes. The technique can also be exploited by multi-host viruses.

1. THE TECHNIQUE

As Windows is backwards compatible with DOS, it can execute the structurally simple `.com`-file format. When a `.com`-file is loaded by Windows (or DOS), it merely loads the file to memory position `0x100` and executes it.

The ELF-header (used in Linux, and many other Unix-like systems) starts with the byte code (“magic number”) `0x7F45`. This is `0x47` in X86 Opcode. Thus, if the file is executed in Windows - it will load the file to `0x100` and jump to `0x147`.

The ELF-header is exactly 52 bytes long. From `/usr/include/elf.h` in a Linux installation, we have

```
typedef struct
{
    unsigned char e_ident[EI_NIDENT]; /* Magic number and other info */
    Elf32_Half e_type; /* Object file type */
    Elf32_Half e_machine; /* Architecture */
    Elf32_Word e_version; /* Object file version */
    Elf32_Addr e_entry; /* Entry point virtual address */
    Elf32_Off e_phoff; /* Program header table file offset */
    Elf32_Off e_shoff; /* Section header table file offset */
    Elf32_Word e_flags; /* Processor-specific flags */
    Elf32_Half e_ehsize; /* ELF header size in bytes */
    Elf32_Half e_phentsize; /* Program header table entry size */
    Elf32_Half e_phnum; /* Program header table entry count */
    Elf32_Half e_shentsize; /* Section header table entry size */
    Elf32_Half e_shnum; /* Section header table entry count */
    Elf32_Half e_shstrndx; /* Section header string table index */
} Elf32_Ehdr;
```

For reference, `Elf32_Half` is 16 bits, `Elf32_Word` is 32 bits and `Elf32_Off` is also 32 bits on the 32 bits X86. If we choose the program header to start directly after this ELF-header, our file continuous as

```
typedef struct
{
    Elf32_Word p_type; /* Segment type */
    Elf32_Off p_offset; /* Segment file offset */
    Elf32_Addr p_vaddr; /* Segment virtual address */
    Elf32_Addr p_paddr; /* Segment physical address */
    Elf32_Word p_filesz; /* Segment size in file */
    Elf32_Word p_memsz; /* Segment size in memory */
    Elf32_Word p_flags; /* Segment flags */
    Elf32_Word p_align; /* Segment alignment */
} Elf32_Phdr;
```

defined in `/usr/include/elf.h`. This brings us to a total header size of `0x54`.

This means the `0x47`'th byte is 13 bytes before the header ends. These bytes specify the size of the file and can thus be chosen in such a way that the instructions executed are harmless. Example of the situation is given by the following code.

```
00000047  0000                add [bx+si], al
00000049  1000                adc [bx+si], al
0000004B  00909090            add [bx+si+0x9090], dl
0000004F  90                  nop
```

where the `0x90` instructions (`bop`) are padded to get us to an instructional boundary. If executed in DOS, we are now in control and can e.g. exit the program.

```
00000050  B44C                mov ah, 0x4c
00000052  CD21                int 0x21
```

2. APPLICATIONS

The `.com`-binary format has a 64 kilo bytes size limitation. This limits the applicability of our technique. However, for many applications, an Internet connection would suffice.

If executed in Linux (or in principle any other ELF-based X86 system) - we have access to the system interrupt `int 0x80`. This gives us basic network and file access. We can even access any external libraries (such as the X-Windows system) through standard means.

However, once executed in Windows, we only have access to DOS. However, once a DOS-program tries to execute a Windows program through `int 0x21` - it will run in Windows. Thus we can either supply a separate file which somehow includes a windows executable, or - more elegantly - include code to generate a Windows executable and execute it.

A proof of concept is found at folk.uio.no/steffen/kapok.tar.gz.